

Monofilament polyester 22/100 braided sleeving



Standards*

- Compliant with directive RoHS 2002/95/CE
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (01-1998) modified by
NF EN 60684-2/A1 (12/2003), NF EN 60684-2/A2 (05/2006)
- NF EN 60684-3 sheets 340 to 342 (4-2003)

Colours and packagings

- Manufactured diameters : 3 to 60 mm
- Standard colour : black or grey
- Standard packaging : rolls
 - diameter 3 to 10 mm : 100 m
 - diameter 12 to 15 mm : 50 m
 - diameter 20 to 60 mm : 25 m
- Other packaging : bobbins
 - diameter 3 to 4 mm : 1000 m
 - diameter 5 to 6 mm : 400 m
 - diameter 8 to 15 mm : 300 m
 - diameter 20 to 25 mm : 200 m
 - diameter 30 mm : 150 m
 - diameter 40 to 60 mm : 100 m

Applications



Inner nominal diameter (mm)	3	4	5	6	8	10	12	15	20	25	30	40	50	60
Inner maximal diameter (mm)	6	8.5	10.5	12	15	19	22	25	30	38	49	64	70	84
Minimum diameter of use (mm)	2	2.5	3	4	5	6.5	8	10	14	16	21	25	32	42
Maximum diameter of use (mm)	5	7	9	10	13	17	19	22	27	35	45	60	65	75

*Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.

