



PEP

Polyester braided sleeving with polyurethane varnish



Standards*

- Compliant with directive RoHS 2002/95/CE
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (01-1998) modified by NF EN 60684-2/A1 (12/2003), NF EN 60684-2/A2 (05/2006)
- NF EN (CEI) 60684-3 sheet 409 (12/1999)

Colours and packagings

- Manufactured diameters : from 0.5 to 12 mm
- Standard colour : white
- Other colours : green, blue, red, black, orange, yellow
- Standard packaging : rolls
 - diameter 0.5 to 4 mm : 200 m
 - diameter 4.5 to 12 mm : 100 m

Applications



Inner diameter (mm)	0.5	0.8	1	1.5	2	2.5	3	3.5	4	4.5	5	6	7	8	9	10	12
Tolerance inner diameter (± mm)	0.15	0.2	0.2	0.2	0.2	0.2	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.3	0.3	0.3	0.3
Minimum wall thickness (mm)	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.35	0.4	0.4	0.4	0.4
Maximum wall thickness (mm)	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.65	0.9	0.9	0.9	0.9

*Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.

