



SCS HT

Fireproof sleeving for high temperatures



Standards*

- Compliant with directive RoHS 2002/95/CE
- NF EN 60695-2 -10 (05-2001)
- NF EN 60695-2 -11 (07-2001)
- NF EN 60684-1 (10-2003)
- NF EN 60684-2 (01-1998)) modified by
NF EN 60684-2/A1 (12/2003), NF EN 60684-2/A2 (05/2006)
- NF EN (CEI) 60684-3 sheets 400 to 402 (02/2003)

Colours and packagings

- Manufactured diameters : from 4 to 45 mm
- Standard colour : brick red
- Other colour : on request
- Standard packagings : bobbins or rolls

Characteristics

- Continuous working temperature : from -60°C to +250°C
- Peaks over 1000°C
- Good resistance to :
 - presence of flames
 - projection of metals or melting glass
 - occasional very high temperature
 - projection of vapour
- Excellent flexibility at low temperatures
- Slight swelling can be caused by hydrocarbons
- Good resistance to UV
- Asbestos free
- Self-extinguishing
- Watertight

Applications



Inner diameter (mm)	4	6	8	10	12	14	16	18	20	22	25	28	30	32	35	38	40	42	45
Tolerance inner diameter (± mm)	0.5	0.5	0.5	0.5	0.5	0.5	1	1	1	1	1	1	1	1	1	1	1	1	1
Wall thickness (mm)	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2

*Our products pass all or parts of requirements for the above-mentioned standards. The technical information written on our datasheets correspond to the most recent knowledges we have on those products, but the user is not exempted to verify the performances in the real particular context of application.

